



TwinLIGHT*, TwinFLASH*

MINI

KÄYTTÖKOHDTE

Kohteisiin, joissa on rajoitettu tilankäyttö; sisä- ja ulkokäyttöön.

TYYPILLISIÄ SOVELLUKSIA

Pienille koneille ja laitteille sekä yleisiin tiloihin.

Valo



12 V AC/DC	
TwinLIGHT	TwinFLASH
Tuotenro	Tuotenro
260 110 74	260 120 74
260 210 74	260 220 74
260 310 74	260 320 74
260 410 74	260 420 74
260 510 74	260 520 74

24 V AC/DC	
TwinLIGHT	TwinFLASH
Tuotenro	Tuotenro
260 110 75	260 120 75
260 210 75	260 220 75
260 310 75	260 320 75
260 410 75	260 420 75
260 510 75	260 520 75

115/230 V AC	
TwinLIGHT	TwinFLASH
Tuotenro	Tuotenro
260 110 60	260 120 60
260 210 60	260 220 60
260 310 60	260 320 60
260 410 60	260 420 60
260 510 60	260 520 60



TriCOLOUR

260 430 75



+ A s e n n u s o s a vaaditaan aina!

Valo + ääni



maks. 95 dB



12 V AC/DC	
TwinLIGHT	TwinFLASH
Tuotenro	Tuotenro
460 110 74	460 120 74
460 210 74	460 220 74
460 310 74	460 320 74
460 410 74	460 420 74
460 510 74	460 520 74

24 V AC/DC	
TwinLIGHT	TwinFLASH
Tuotenro	Tuotenro
460 110 75	460 120 75
460 210 75	460 220 75
460 310 75	460 320 75
460 410 75	460 420 75
460 510 75	460 520 75

115/230 V AC	
TwinLIGHT	TwinFLASH
Tuotenro	Tuotenro
460 110 60	460 120 60
460 210 60	460 220 60
460 310 60	460 320 60
460 410 60	460 420 60
460 510 60	460 520 60

+ A s e n n u s o s a vaaditaan aina!

Ääni



maks. 95 dB



12 V AC/DC
Tuotenro 160 700 74

24 V AC/DC
Tuotenro 160 700 75

115/230 V AC
Tuotenro 160 700 60

+ A s e n n u s o s a vaaditaan aina!

Asennusosat



Pinta-asennus



Tuotenro 260 700 01

Reikäasennus M 22



Tuotenro 260 700 03

Reikäasennus PG 29



Tuotenro 260 700 04

Putkiasennus



Tuotenro 260 700 05

Seinäasennus holkittivisteellä



Tuotenro 260 700 06

Seinäasennus



Tuotenro 260 700 07